

5

10

15

SPECIFICATION

TO WHOM IT MAY CONCERN

Be it known that we, PRIMOT Jérôme and GUERINEAU Nicolas,
citizens of the French Republic and residing at :

20

- 35 avenue de Paris, 92320 CHATILLON, FRANCE
- 42 avenue Rabelais, 92160 ANTONY, FRANCE

have invented new and useful improvements in :

25

**Achromatic optical interferometer with continuously
adjustable sensitivity**

of which the following is a specification :

BACKGROUND OF THE INVENTION

1 - Field of the Invention

5 The invention relates to the analysis of the wavefront of a light beam.

2 - Description of the Prior Art

10 This type of analysis is used to test optical components, to qualify optical devices and to control deformable optical components used in active or adaptive optics. It is also used to study physical phenomena which cannot be measured directly, such as variations of
15 the optical index within turbulent media encountered on passing through the terrestrial atmosphere or in a wind tunnel. It is also used to test the flatness of electronic components, for example matrix focal planes, and for shaping power laser beams.

20

 The type of wavefront analysis to which the invention relates is based on the use of a diffraction grating positioned on the path of the beam to be analyzed.

25

 To make the following description easier to understand, a grating of the above kind is defined as an optical system introducing periodic variations of phase, intensity, or phase and intensity. Any grating is
30 therefore characterized by the multiplication of two functions : the one, called as a phase function,

representing periodic variations of phase introduced by the grating and the other one, called as an intensity function, representing periodic variations of intensity introduced by the grating.

5

French patent application No. 2,712,978 outlines the mode of construction and definition of a two-dimensional grating. A set of points disposed regularly in two directions constitutes a plane meshing. The points
10 define an elementary mesh. The elementary mesh is the smallest surface for paving the plane without gaps in the two directions defining it. The polygon of the elementary mesh is the minimum surface polygon whose sides are supported by the mediatrices of the segments
15 connecting any point of the set to its nearest neighbors. A two-dimensional grating is the intentional repetition of an elementary pattern disposed in accordance with a plain meshing. A plain meshing can define hexagonal or rectangular elementary meshes (square meshes are merely a
20 special case of rectangular meshes).

When a diffraction grating is illuminated with a light beam, called as an incident beam, the light beams diffracted by the grating, called as emergent beams, can
25 be described using two equivalent approaches.

The first approach considers the emergent beams as replicas of the incident beam. They are referred to as sub-beams, each corresponding to one order of diffraction
30 of the grating.

The second approach considers the emergent beams as beams diffracted by each mesh of the grating. They are referred to as secondary beams.

5 When an intensity function is introduced by a grating, each secondary beam originates from a sub-pupil.

10 The Hartmann-Shack analyzer is known by the article "PHASE MEASUREMENTS SYSTEMS FOR ADAPTIVE OPTICS", J.C. WYANT, AGARD Conf. Proc., N°300, 1981. The general principle of its operation is optical conjugation of the phase error to be analyzed with an analysis plane containing an array of microlenses which defines a two-dimensional grating made up of a phase function, each
15 microlens delimiting a secondary beam. In the common plane of the foci of the microlenses, referred to as the observation plane, two-dimensional meshing of spots deformed according to the slopes of the wavefront is observed. For active or adaptive optical control
20 applications, the preferred meshing is rectangular. The foregoing description is based on a conventional description of the Hartmann-Shack analyzer and on the approach of decomposition into secondary beams. Another interpretation based on decomposition into sub-beams
25 diffracted by the array of microlenses is outlined in the publication "Variations on a Hartmann theme", F. Roddier, SPIE, TUXON 1990.

30 That type of analyzer has the advantage of working in polychromatic light, provided that the path difference error to be detected does not depend on the wavelength.

It is very simple to use, consisting of a single optical component, and its optical efficiency is very high. However, its sensitivity and dynamic range can be adjusted only by changing the array of microlenses. In an analysis mode referred to as the undersampled mode it can also be used to analyze the wavefront obtained from low-intensity light sources. This analysis mode uses a small number of microlenses, regardless of the wavefront to be measured, in order to concentrate the low usable flux at a few points where the slope of the wavefront is measured.

French patent application No. 2,712,978, already mentioned, describes a three-wave lateral shear interferometer using a two-dimensional phase and/or intensity grating and a spatial filtering system. Using the approach of decomposition into sub-beams, the grating optically subdivides the incident beam to be analyzed into three sub-beams in a conjugate plane of the error. Particular optical processing of the three sub-beams obtained in this way produces an interferogram consisting of a hexagonal meshing of light spots whose contrast does not vary, regardless of the observation plane used. The interferogram is sensitive to the slopes of the wavefront, and offers the possibility of continuous adjustment of the dynamic range and sensitivity. The observation distance is defined as the distance between the observation plane and the zero sensitivity plane, which is a plane conjugate with the plane of the grating downstream of the spatial filter. In the article "Achromatic three-wave (or more) lateral shearing

interferometer", Journal of Optical Society of America A, volume 12, N°12, December 1995, pages 2679-2685, there is an outline description of a modification of the above interferometer toward a four-wave lateral shear
5 interferometer in which the two-dimensional meshing of the light spots observed in the interferogram is rectangular and therefore better suited to active or adaptive optical control applications.

10 This type of analyzer is achromatic and its luminous efficiency is close to that of the Hartmann-Shack analyzer. On the other hand, it is more complex to use because of the insertion of the spatial filtering system for selecting the sub-beams between the grating and the
15 observation plane of the interference fringe system. Also, the spatial filtering system imposes limitations on measuring light beams with a high level of interference or a very large bandwidth. It therefore cannot use the undersampled analysis mode referred to in connection with
20 the Hartmann-Shack analyzer.

It would therefore appear to be strongly desirable to have an interferometer combining the simplicity of use and operating capacity of the Hartmann-Shack analyzer,
25 from low-intensity light sources with high levels of interference or very large bandwidth, and the flexible adjustment of the dynamic range of the three-wave lateral shear interferometer described in French patent application No. 2,712,978 or the four-wave lateral shear
30 interferometer outlined in the article "Achromatic three-wave (or more) lateral shearing interferometer".

OBJECT OF THE INVENTION

5 The object of the present invention is to make progress in this direction.

SUMMARY OF THE INVENTION

10 The invention can be considered in the form of a method or a system.

15 The method of analyzing the wavefront of a light beam according to the invention is of the type wherein a two-dimensional diffraction grating with rectangular meshing is placed in a plane which is perpendicular to the light beam to be analyzed and which is optically conjugated with a plane of analysis of the wavefront, thereby multiplying an intensity function by a phase function and causing through these functions the beam to be diffracted into different beams emergent from the grating. The intensity function defines a rectangular meshing of sub-pupils in the two-dimensional meshing transmitting the light from the light beam to be analyzed to form a plurality of secondary beams disposed in accordance with the rectangular meshing. The phase function introduces a phase shift between two adjacent secondary beams such that the two adjacent secondary beams are in phase opposition. An image formed by interference between the emergent secondary beams is created and observed in a plane located at a predetermined distance from the perpendicular plane.

20

25

30

Deformations in the image is related to the slopes of the analyzed wavefront.

5 The expression "phase opposition" must be understood as also meaning phase shifts substantially adjoining absolute phase opposition.

10 Thanks to the above, the diffraction grating multiplying the two functions defined in this way diffracts a rectangular meshing of secondary beams which propagate and interfere with each other to generate an image in any observation plane parallel to the plane of the grating, the image taking the form of a rectangular meshing of light spots whose contrast is substantially
15 independent of the wavelength and of the observation distance.

20 The rectangular meshing of the light spots can be observed in the plane of the grating (zero sensitivity plane). The meshing is advantageously observed in a plane at an observation distance chosen by the user according to the slopes of the wavefront to be analyzed and the required dynamic range.

25 This method works in polychromatic light and can be used to measure beams with a high level of interference, offering continuous adjustment of the sensitivity and the dynamic range of the system by adjusting the observation distance.

30

The user therefore has the benefit of the

flexibility of continuous adjustment of the dynamic range of the four-wave lateral shear interferometer without the user constraints associated with the insertion of the spatial filtering system.

5

The invention also encompasses systems for implementing the light beam wavefront analyzing method. Such a system comprises input optics optically conjugating a reference plane with a plane in which the wavefront is analyzed and a two-dimensional diffraction grating with rectangular meshing in the reference plane. The grating causes diffraction of the beam into different emergent beams, and comprises an intensity beam and a phase grating. The intensity grating has an elementary intensity mesh in which an elementary intensity pattern is disposed and which is of length L in a first direction of the rectangular meshing and of width l in a second direction of the rectangular meshing. The phase grating has an elementary phase mesh in which an elementary phase pattern is disposed and which is of length $2L$ in the first direction of the rectangular meshing of the phase grating and of width $2l$ in the second direction of the rectangular meshing of the phase grating. The sides of the elementary meshes of the phase grating coincide with sides of the elementary meshes of the intensity grating. The elementary phase pattern introduces a phase shift close to π (modulo 2π) between two secondary beams passing through two adjacent elementary intensity patterns. The system also comprises means for observing an image formed by interference between the emergent secondary beams, deformations in the image being related

to the slopes of the analyzed wavefront.

5 A preferred intensity two-dimensional grating according to the invention has a rectangular intensity elementary pattern whose area is close to 50% of the area of the intensity elementary mesh.

10 A preferred two-dimensional phase grating according to the invention, made from a material having a particular thickness and a transmission index, has a four-square checkerboard phase elementary pattern, each square of the checkerboard having the length L and the width l of the intensity elementary mesh, two adjacent squares having different thicknesses performed the
15 defined phase function by varying the index.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Further features and advantages of the invention will be apparent from the following particular description of several preferred embodiments of the invention shown in the corresponding accompanying drawings, in which:

25 - FIG. 1A is a theoretical optical diagram of a system for implementing the invention for testing optical components;

30 - FIG. 1B is a theoretical optical diagram of a system for measuring turbulent media, such as the terrestrial atmosphere, through which passes a beam from

a polychromatic source such as a star;

- FIG. 2 shows a rectangular meshing two-dimensional grating;

5

- FIG. 3A shows one example of a rectangular meshing intensity grating that can be used in the invention;

10

- FIG. 3B shows one example of a square meshing intensity grating that can be used in the invention;

- FIG. 4 shows one example of a rectangular meshing phase grating that can be used in the invention; and

15

- FIG. 5 shows one example of a rectangular meshing grating according to the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

20

FIGS. 1A and 1B show two examples of systems for implementing the invention.

25

30

In FIG. 1A, a polychromatic light source S is placed at the focus of a collimating lens O_1 . The parallel light beam leaving the lens O_1 illuminates a sample to be tested, which is shown diagrammatically as a plate 1A with parallel faces, placed in the plane P_D and having a flatness error D_1 . The sample can be any other optical system (a lens or a mirror, in particular a telescope mirror), or simply a region of a gaseous medium disturbed by a flow, for example.

FIG. 1B illustrates a system for implementing the invention in the case of an application to astronomy. A plane wave from a very distant source such as a star, for example, passes through a turbulent medium whose index variations are represented by sinuous lines.

An input arrangement provides the optical adaptation necessary for implementing the process according to the invention.

This adaptation is preferably performed by an afocal system consisting of two lenses O_2 and O_4 with a field lens O_3 at an intermediate position. The functions of the afocal system are to match the diameter of the beam analyzed in the plane P_D to the dimensions of the two-dimensional grating in a plane P_C and to conjugate the plane P_D containing the error to be analyzed optically with the plane P_C .

Other means can be used to achieve this optical conjugation of the two planes.

A two-dimensional grating GR able to combine intensity and phase functions is placed in the analysis plane P_C . This grating can consist of two gratings GI3A, GP4 or more, like that shown in FIG. 5, for example. It is the particular combination of functions that characterizes the grating of the invention, rather than a particular embodiment.

In the example of embodiment shown, the grating GR is made up of an intensity grating GI and a phase grating GP.

5 The intensity grating GI implements an intensity function FI which defines a rectangular meshing of sub-pupils transmitting the light of the beam to be analyzed in the form of a plurality of secondary beams.

10 The phase grating GP implements a phase function FP which introduces a mean phase shift between two adjacent secondary beams close to π (modulo 2π).

15 The order in which the two functions are effected in the plane is of no importance.

According to the invention, the interferogram is made up of a rectangular meshing of spots.

20 The plane P_c is a zero sensitivity plane.

The observation is effected in a plane P_s located at a chosen observation distance d from the plane P_c .

25 The dynamic range and sensitivity of the system vary with the observation distance. Thus if d is zero, the observation plane is coincident with the analysis plane P_c in which the grating is located and the sensitivity is zero.

30

In general, it is possible to use additional means

of observing the plane P_s , for example a lens which optically conjugates the plane P_s and a more accessible working plane.

5 FIG. 2 shows a rectangular meshing two-dimensional grating GR characterized by a rectangular elementary mesh of length L and width l . The meshing, represented in chain-dotted line, is not necessarily visible in the final grating. In each mesh, a pattern MO is shown which
10 introduces variations of the intensity and/or phase of the incident light beam.

FIGS. 3A and 3B show two-dimensional intensity gratings GI which offer a simple means of implementing
15 the intensity function of the method according to the invention. FIG. 3A shows a crossed Ronchi grating GI3A with a rectangular meshing of length L and width l . The shaded areas are areas of zero transmission and the clear areas can be either transparent or reflecting. These
20 clear areas constitute sub-pupils. The dimensions L_1 and l_1 of these transparent areas are preferably close to $2L/3$ and $2l/3$, respectively. The area of each sub-pupil is therefore close to half the area of the elementary mesh of the rectangular meshing. FIG. 3B shows a crossed
25 Ronchi grating GI3B with a square mesh of side length L , which is deemed to constitute the most advantageous embodiment of the invention.

FIG. 4 is a perspective view of one example of a
30 two-dimensional phase grating GP which offers a simple means of implementing the phase function of the method

according to the invention. FIG. 4 shows a rectangular meshing checkerboard grating GP4 with side length 2L and 2l, e.g. with two levels of thickness. The grating GP4 has stepped periodic thickness variations so that the thickness difference e between adjacent steps or levels satisfies the equation:

$$e = \lambda/n \cdot (k + \frac{1}{2}),$$

where λ is the mean operating wavelength,
n is
- either the refractive index of the material when the phase grating is used in transmission mode, or
- twice the refractive index of the transmission medium
when the phase grating is used in reflection mode,
and k is an integer.

The shaded areas of the grating GP4 can be transparent for a grating used in transmission mode or reflecting for a grating used in reflection mode.

An advantageous means of implementing the gratings GI and GP is to use the masking and photolithographic etching techniques widely used in the semiconductor industry; thus GI can be implemented by depositing a metal mask onto a substrate wafer and GP by etching a substrate wafer. With these techniques it is possible to make a two-dimensional phase and intensity grating which combines the FI and FP functions of gratings GI and GP, respectively, from a single substrate plate.

Other methods of implementing the two functions FI and FP with gratings GI and GP can be envisaged, for example based on registering interferograms on photosensitive plates to produce holographic gratings.

5

Combining the GI and GP gratings generates a meshing of light spots whose contrast is substantially independent of the observation distance d and the wavelength used. Because of the sudden intensity variations caused by the Ronchi intensity grating GI, contrast fluctuations occur during propagation which cause high-frequency local deformation of the light spots. These unwanted deformations remain small compared to the sinusoidal intensity modulation observed in the two directions and do not interfere with the analysis of the wavefront.

10

15

French patent application No. 2,682,761 proposes a technique for analyzing the interference images obtained in order to obtain the slopes of the wavefront. Those techniques can be applied directly to the meshings of lights spots obtained in accordance with the present invention.

20

25

The grid of the deformations of the meshing of light spots can also be obtained by calculating the position of the barycenters of the light spots. This technique is routinely employed in the case of a Hartmann-Shack analyzer and can be applied directly to the rectangular meshings of light spots obtained in accordance with the present invention.

30